

AktiMate Mini

Specification

| | |
|----------------------------------|--|
| Configuration | 2-Way Active Bookshelf Speakers (1 Active master speaker and 1 Passive slave speaker) |
| Power Output | 40W into its own 4 Ohm speaker load |
| Woofers | 130mm (5.25 ins) mid/bass with moulded polypropylene cone. Shielded magnet. (Licensed from Epos Ltd - U.K.) |
| Tweeter | 25 mm (1 in) metal dome with neodymium magnet (Licensed from Epos Ltd. - U.K.) |
| Frequency Response | 50Hz - 22kHz +/- 1.5dB |
| Power Amplifier | Type Class A/B (built in) 40 Watts per channel RMS Nat-Semi LM4766 Overture™ Burr-Brown PGA2311 digitally controlled analogue volume control |
| Transformer | 120W Toroidal power transformer |
| Inputs | 1 Pair RCA Stereo Sockets 1 x 3.5 mm Jack plug Apple iPod dock |
| Outputs | 1 Pair RCA Stereo Sockets (un-filtered) for connection of subwoofer or to daisy-chain to second pair Video output |
| Connections | USB (for charging iPod or MP3 players only) |
| THD | <0.05% |
| Crosstalk | <50dB |
| Input Impedance | 10k Ohms unbalanced |
| Passive Speaker Impedance | 4 Ohms |
| Protection | Output current limiting, thermal over-temperature, power on/off transient protection, replaceable external mains fuse |
| Mains Voltage | 240/120V 50/60Hz |
| Inclusions | Right angled IEC power cord 3-metres of connecting speaker cable iPod connector accessory pack IR remote control handset 4mm Banana plugs |
| Size | 300 x 185 x 210 mm 12 x 7½ x 8½ ins |
| Weight | 12 Kgs 26½ lbs |
| Packed | 1 carton |