

Main Speaker - Audio Technology Series >> ATS-4 (ATS-4)

Acoustically neutral fibre board cabinet - Epoxy glued cladding - PVA glue used in all joints - Rear vented, Low Q Ratio alignment - Tandem woofers - Cloth speaker cone surrounds - Two layer speaker cone construction - Separate mid-range sub enclosure - Impregnated Polyester dome - Feron hemisphere - Highly stable vitrified Y35 magnets - Very large, high flux magnets - Polyester Imide voice coil windings - High input power tolerance - Phase compensated cross-over - Non ageing cross-over components - Bi wiring gold banana terminals - Wide environmental tolerance - 10 year warranty.



Technical specifications for ATS-4

Model: ATS-4
Woofers: 2 x 173 (mm)
MR: 136 (mm)
Tweeter: 25 (mm)
Frequency: 35-23 (Hz - kHz)
Sensitivity: 93 (dbSPL)
Nominal Impedance: 6 (ohms)

Cabinet Dimensions: 21 x 41 x 92 (WxDxH)
Amplifier Power: 160 (Watts)
Bi Wire: Yes
Shielded: No
Spikes: Yes
Bass: Low Q Ratio
Weight: 18.00 (Kg)
Colour: Black (two types) or Cherry

RRP: \$1299.00 **WARRANTY:** 10 Years

[Close window >>](#)

AARON LOUDSPEAKERS
BETETEC INDUSTRIES PTY LTD
17 De Havilland Crescent Ballina NSW 2478
Phone 02 6686 0277 | speakers@aaronhifi.com.au